



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/036,304	12/28/2001	Tara A. Burnhouse	871.0103.U1(US)	2753
29683	7590	12/28/2004	EXAMINER	
HARRINGTON & SMITH, LLP 4 RESEARCH DRIVE SHELTON, CT 06484-6212			MILORD, MARCEAU	
			ART UNIT	PAPER NUMBER
			2682	

DATE MAILED: 12/28/2004

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary	Application No.	Applicant(s)	
	10/036,304	BURNHOUSE ET AL.	
	Examiner	Art Unit	
	Marceau Milord	2682	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
 - If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
 - If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
 - Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
- Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 03 August 2004.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-21 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-21 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
- Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
- Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. _____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|---|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413) |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____ |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Claim Rejections - 35 USC § 103

1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

2. Claims 1- 21 are rejected under 35 U.S.C. 103(a) as being unpatentable over Walsh et al (US Patent No 6144848) in view of Herrod et al (US Patent No 6405049 B2) and Soini et al (US Patent No 6445932 B1).

Regarding claims 1 and 3, Walsh et al discloses a system (figs. 1-3) for displaying data transfer rates on a display comprising: a system for displaying the transfer rates in an alphanumeric mode or an alternative graphics mode (col. 3, line 40- col. 4, line 8; col. 17, line 5- col. 18, line 41; col. 4, lines 10-47; col. 17, line 5- col. 18, line 41; col. 35, line 21- col. 36, line 26).

However, Walsh et al does not specifically disclose the features of a system for switching between displaying the transfer rates in the alphanumeric mode and the graphics mode.

On the other hand, Herrod et al, from the same field of endeavor, discloses a portable data device and a cradle for receiving the portable data device. The cradle is arranged to recharge the portable data device power supply and/or upload or download information to and from the portable data device. In addition, the user input comprises a keyboard with which the user can input information to the terminal (col. 2, line 55- col. 3, line 61). The terminal also includes a display for displaying information to the user. The cradle interface allows downloading of data stored in the terminal to the cradle as well as transfer of control or other data from the cradle to the terminal (col. 5, line 34- col. 6, line 67). The information transmitted by the access points to the terminal can take various forms (col. 10, line 37- col. 11, line 59; col. 17, line 15- col. 18, line 59).

Soini also discloses a multi-service mobile station that comprises a module for connecting the device by radio to a telecommunication network in order to utilize typical mobile station services, such as speech and data services. Additionally, the multi-service mobile station provides processing memory for using various information processing services, such as telefax service and electronic mail service. The criteria are shifting from one service to another, going over the current saving mode, or, in two-section multi-service terminal device, folding the device together, and switching off the display (col. 2, line 37-col. 3, line 45). Furthermore, the user can set the multi-service mobile station to automatic answering mode for telefax messages, short messages, such as SMS messages (col. 4, line 30-col. 5, line 60). In addition, the user can move from a first service to a second service by pushing menu keys (col. 6, line 32- col. 7, line 65). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Soini to the modified system of Herrod and Walsh in order to

Art Unit: 2682

provide a multi-service mobile station with a touch sensitive surface enabling using the display for receiving alphanumeric and graphic information.

Regarding claim 2, Walsh et al as modified discloses a system (figs. 1-3) for displaying data transfer rates on a display, wherein the system for switching comprises a keypad on a portable radio communication device (col. 15, lines 24- 32; col. 25, lines 35-44; col. 29, lines 3-15; col. 33, lines 10-25).

Regarding claim 4, Walsh et al as modified discloses a system (figs. 1-3) for displaying data transfer rates on a display, wherein the system for switching comprises a menu selectable feature displayed on the display (col. 4, lines 10-47; col. 35, line 21- col. 36, line 26).

Regarding claim 5, Walsh et al as modified discloses a system (figs. 1-3) for displaying data transfer rates on a display, further comprising a system for inactivating display of the data transfer rate on the display (col. 17, line 5- col. 18, line 41).

Regarding claim 6, Walsh et al as modified discloses a system (figs. 1-3) for displaying data transfer rates on a display, wherein the system for switching comprises means for not displaying the transfer rates in either the alphanumeric mode or the graphics mode (col. 18, line 34- col. 19, line 33).

Regarding claim 7, Walsh et al as modified discloses a mobile radio telephone (figs. 1-5) comprising: a display; a transceiver; and a controller coupled to the display and the transceiver (col. 25, lines 17-67), wherein the controller further comprises the system for displaying data transfer rates (col. 20, line 24- col. 21, line 16).

However, Walsh et al does not specifically disclose a system for switching between displaying the transfer rates in the alphanumeric mode and the graphics mode.

On the other hand, Herrod et al, from the same field of endeavor, discloses a portable data device and a cradle for receiving the portable data device. The cradle is arranged to recharge the portable data device power supply and/or upload or download information to and from the portable data device. In addition, the user input comprises a keyboard with which the user can input information to the terminal (col. 2, line 55- col. 3, line 61). The terminal also includes a display for displaying information to the user. The cradle interface allows downloading of data stored in the terminal to the cradle as well as transfer of control or other data from the cradle to the terminal (col. 5, line 34- col. 6, line 67). The information transmitted by the access points to the terminal can take various forms (col. 10, line 37- col. 11, line 59; col. 17, line 15- col. 18, line 59).

Soini also discloses a multi-service mobile station that comprises a module for connecting the device by radio to a telecommunication network in order to utilize typical mobile station services, such as speech and data services. Additionally, the multi-service mobile station provides processing memory for using various information processing services, such as telefax service and electronic mail service. The criteria are shifting from one service to another, going over the current saving mode, or, in two-section multi-service terminal device, folding the device together, and switching off the display (col. 2, line 37-col. 3, line 45). Furthermore, the user can set the multi-service mobile station to automatic answering mode for telefax messages, short messages, such as SMS messages (col. 4, line 30-col. 5, line 60). In addition, the user can move from a first service to a second service by pushing menu keys (col. 6, line 32- col. 7, line 65). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Soini to the modified system of Herrod and Walsh in order to

Art Unit: 2682

provide a multi-service mobile station with a touch sensitive surface enabling using the display for receiving alphanumeric and graphic information.

Regarding claim 8, Walsh et al as modified discloses a mobile radio communication device (figs. 1-5) having a display and a transceiver for transmitting and receiving data, the improvement comprising: means for displaying a data transfer rate of data with the transceiver on the display in an alphanumeric format (col. 33, lines 10-25; col. 31, lines 16- 37).

Regarding claim 9, Walsh et al as modified discloses a mobile radio communication device (figs. 1-5) further comprising means for displaying the data transfer rate on the display in a graphical format (col. 4, lines 10- 47; col. 35, line 21- col. 36, line 26).

However, Walsh et al does not specifically disclose a means for switching between displaying the transfer rates in the alphanumeric mode and the graphics mode.

On the other hand, Herrod et al, from the same field of endeavor, discloses a portable data device and a cradle for receiving the portable data device. The cradle is arranged to recharge the portable data device power supply and/or upload or download information to and from the portable data device. In addition, the user input comprises a keyboard with which the user can input information to the terminal (col. 2, line 55- col. 3, line 61). The terminal also includes a display for displaying information to the user. The cradle interface allows downloading of data stored in the terminal to the cradle as well as transfer of control or other data from the cradle to the terminal (col. 5, line 34- col. 6, line 67). The information transmitted by the access points to the terminal can take various forms (col. 10, line 37- col. 11, line 59; col. 17, line 15- col. 18, line 59).

Soini also discloses a multi-service mobile station that comprises a module for connecting the device by radio to a telecommunication network in order to utilize typical mobile station services, such as speech and data services. Additionally, the multi-service mobile station provides processing memory for using various information processing services, such as telefax service and electronic mail service. The criteria are shifting from one service to another, going over the current saving mode, or, in two-section multi-service terminal device, folding the device together, and switching off the display (col. 2, line 37-col. 3, line 45). Furthermore, the user can set the multi-service mobile station to automatic answering mode for telefax messages, short messages, such as SMS messages (col. 4, line 30-col. 5, line 60). In addition, the user can move from a first service to a second service by pushing menu keys (col. 6, line 32- col. 7, line 65). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Soini to the modified system of Herrod and Walsh in order to provide a multi-service mobile station with a touch sensitive surface enabling using the display for receiving alphanumeric and graphic information.

Regarding claim 10, Walsh et al as modified discloses a mobile radio communication device (figs. 1-5), wherein the means for switching comprises a user actuatable keypad (col. 4, lines 10- 47; col. 35, line 21- col. 36, line 26).

Regarding claims 11-13, Walsh et al discloses a mobile radio communication device (figs. 1-5) comprising: a transceiver; a controller coupled to the transceiver; a display coupled to the controller, wherein the controller is adapted to display on the display a data transfer rate of data by the transceiver (col. 33, lines 10-25; col. 31, lines 16- 37; col. 4, lines 10-47; col. 17, line 5- col. 18, line 41; col. 35, line 21- col. 36, line 26).

However, Walsh et al does not specifically disclose the features of a system for inactivating display of the data transfer rate on the display while the transceiver is transmitting or receiving the data; wherein the controller is adapted to display the data transfer rate in either an alphanumeric format or a graphical format; a system for allowing a user to switch between display of the data transfer rate in either the alphanumeric format or the graphical format.

On the other hand, Herrod et al, from the same field of endeavor, discloses a portable data device and a cradle for receiving the portable data device. The cradle is arranged to recharge the portable data device power supply and/or upload or download information to and from the portable data device. In addition, the user input comprises a keyboard with which the user can input information to the terminal (col. 2, line 55- col. 3, line 61). The terminal also includes a display for displaying information to the user. The cradle interface allows downloading of data stored in the terminal to the cradle as well as transfer of control or other data from the cradle to the terminal (col. 5, line 34- col. 6, line 67). The information transmitted by the access points to the terminal can take various forms (col. 10, line 37- col. 11, line 59; col. 17, line 15- col. 18, line 59).

Soini also discloses a multi-service mobile station that comprises a module for connecting the device by radio to a telecommunication network in order to utilize typical mobile station services, such as speech and data services. Additionally, the multi-service mobile station provides processing memory for using various information processing services, such as telefax service and electronic mail service. The criteria are shifting from one service to another, going over the current saving mode, or, in two-section multi-service terminal device, folding the device together, and switching off the display (col. 2, line 37-col. 3, line 45). Furthermore, the user can

Art Unit: 2682

set the multi-service mobile station to automatic answering mode for telefax messages, short messages, such as SMS messages (col. 4, line 30-col. 5, line 60). In addition, the user can move from a first service to a second service by pushing menu keys (col. 6, line 32- col. 7, line 65). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Soini to the modified system of Herrod and Walsh in order to provide a multi-service mobile station with a touch sensitive surface enabling using the display for receiving alphanumeric and graphic information.

Regarding claim 14, Walsh et al as modified discloses a mobile radio communication device (figs. 1-5), wherein the system for allowing a user to switch between display formats comprises a menu selectable feature (col. 4, lines 10- 47; col. 35, line 21- col. 36, line 26).

Regarding claim 15, Walsh et al as modified discloses a mobile radio communication device (figs. 1-5), wherein the menu selectable feature also allows the user to activate the system for inactivating display of the data transfer rate (col. 17, line 5- col. 18, line 41).

Claims 16 contains similar limitations addressed in claim 11, and therefore is rejected under a similar rationale.

Regarding claims 17-18, Walsh et al discloses a method (figs. 1-3) of displaying a data transfer rate on a display, the method comprising steps of: selecting, by a user, a data transfer rate display mode from a plurality of data transfer rate display modes (col. 3, line 40- col. 4, line 8; col. 17, line 5- col. 18, line 41; col. 4, lines 10-47; col. 17, line 5- col. 18, line 41; col. 35, line 21- col. 36, line 26).

However, Walsh et al does not specifically disclose the features of displaying the data transfer rate on the display based upon the selected data transfer rate display mode, wherein the

Art Unit: 2682

plurality of data transfer rate display modes comprises an alphanumeric display mode and a graphical display mode

On the other hand, Herrod et al, from the same field of endeavor, discloses a portable data device and a cradle for receiving the portable data device. The cradle is arranged to recharge the portable data device power supply and/or upload or download information to and from the portable data device. In addition, the user input comprises a keyboard with which the user can input information to the terminal (col. 2, line 55- col. 3, line 61). The terminal also includes a display for displaying information to the user. The cradle interface allows downloading of data stored in the terminal to the cradle as well as transfer of control or other data from the cradle to the terminal (col. 5, line 34- col. 6, line 67). The information transmitted by the access points to the terminal can take various forms (col. 10, line 37- col. 11, line 59; col. 17, line 15- col. 18, line 59).

Soini also discloses a multi-service mobile station that comprises a module for connecting the device by radio to a telecommunication network in order to utilize typical mobile station services, such as speech and data services. Additionally, the multi-service mobile station provides processing memory for using various information processing services, such as telefax service and electronic mail service. The criteria are shifting from one service to another, going over the current saving mode, or, in two-section multi-service terminal device, folding the device together, and switching off the display (col. 2, line 37- col. 3, line 45). Furthermore, the user can set the multi-service mobile station to automatic answering mode for telefax messages, short messages, such as SMS messages (col. 4, line 30- col. 5, line 60). In addition, the user can move from a first service to a second service by pushing menu keys (col. 6, line 32- col. 7, line 65).

Art Unit: 2682

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Soini to the modified system of Herrod and Walsh in order to provide a multi-service mobile station with a touch sensitive surface enabling using the display for receiving alphanumeric and graphic information.

Regarding claim 19, Walsh et al as modified discloses a method (figs. 1-3) of displaying a data transfer rate on a display, wherein the plurality of data transfer rate display modes further comprises an OFF display mode which prevents displaying of the data transfer rate on the display (col. 15, line 20- col. 16, line 7).

Regarding claim 20, Walsh et al as modified discloses a method (figs. 1-3) of displaying a data transfer rate on a display, wherein the step of selecting a data transfer rate display mode comprises selecting the display model from a menu of available display modes displayed on the display (col. 4, lines 10- 47; col. 35, line 21- col. 36, line 26).

Regarding claim 21, Walsh et al discloses a method (figs. 1-3) of changing displaying of a data transfer rate on a display of a portable communication device, the method comprising steps of: selecting, by a user, to turn a displaying feature of the data transfer rate ON or OFF (col. 15, line 8- col. 16, line 57); and during data transfer by the portable communication device, a controller of the portable communication device, connected to the display (col. 31, lines 16-37; col. 35, line 21- col. 36, line 33; col. 19, line 23- col. 20, line 53; col. 22, lines 7- 23; col. 33, lines 10-25).

However, Walsh et al does not specifically disclose the step of preventing the display from displaying the data transfer rate when the user has selected to turn the displaying feature OFF.

On the other hand, Herrod et al, from the same field of endeavor, discloses a portable data device and a cradle for receiving the portable data device. The cradle is arranged to recharge the portable data device power supply and/or upload or download information to and from the portable data device. In addition, the user input comprises a keyboard with which the user can input information to the terminal (col. 2, line 55- col. 3, line 61). The terminal also includes a display for displaying information to the user. The cradle interface allows downloading of data stored in the terminal to the cradle as well as transfer of control or other data from the cradle to the terminal (col. 5, line 34- col. 6, line 67). The information transmitted by the access points to the terminal can take various forms (col. 10, line 37- col. 11, line 59; col. 17, line 15- col. 18, line 59).

Soini also discloses a multi-service mobile station that comprises a module for connecting the device by radio to a telecommunication network in order to utilize typical mobile station services, such as speech and data services. Additionally, the multi-service mobile station provides processing memory for using various information processing services, such as telefax service and electronic mail service. The criteria are shifting from one service to another, going over the current saving mode, or, in two-section multi-service terminal device, folding the device together, and switching off the display (col. 2, line 37-col. 3, line 45). Furthermore, the user can set the multi-service mobile station to automatic answering mode for telefax messages, short messages, such as SMS messages (col. 4, line 30-col. 5, line 60). In addition, the user can move from a first service to a second service by pushing menu keys (col. 6, line 32- col. 7, line 65). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Soini to the modified system of Herrod and Walsh in order to

Art Unit: 2682

provide a multi-service mobile station with a touch sensitive surface enabling using the display for receiving alphanumeric and graphic information.

Response to Arguments

3. Applicant's arguments with respect to claims 1-21 have been considered but are moot in view of the new ground(s) of rejection.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Marceau Milord whose telephone number is 703-306-3023. The examiner can normally be reached on Monday-Thursday.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Vivian C. Chin can be reached on 703-308-6739. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

MARCEAU MILORD


MARCEAU MILORD
PRIMARY EXAMINER

Marceau Milord

Examiner

Art Unit 2682

12-26-04

Application/Control Number: 10/036,304

Page 14

Art Unit: 2682